

**INSTRUMENT APPROACH  
CHART (IAC)**

**BAURU / Bauru (SBBU)**

**AD ELEV: 2025'**

**RNAV(GNSS) Z RWY 32**



ATIS <b>127.875</b>	APP BAURU <b>121.30</b>	AFIS BAURU <b>121.30</b>	GNDC <b>NIL</b>
<b>N/A</b>	FINAL CRS <b>323°</b>	FAF <b>3670'</b>	LNAV/VNAV DA / (OCH): <b>2330' (310')</b>
			LNAV MDA / (OCH): <b>2420' (400')</b>

APCH Perdida: Subir para **5000'**, rumo **323** até BU011. Após, curva à **ESQUERDA**, rumo **308** até BU013 para espera.

Missed APCH: Climb to **5000'**, course **323** to BU011. Then, turn **LEFT**, course **308** to BU013 for holding.

RMK: 1) Para sistemas não compensados Baro-VNAV, LNAV/VNAV NAO AUTORIZADO abaixo de 5°C ou acima de 40°C.

1) For uncompensated systems Baro-VNAV, LNAV/VNAV NOT AUTHORIZED below 5°C or above 40°C.



	RWY32	1.1	2.0	3.0	4.0	BU016	KT	090	110	130	150	170	190
	ALT	2420	2709	3027	3346	3670	FPM	500	600	700	800	950	1050
	(HGT)	400	687	1005	1324	1650	FAF-MAPT	NA					

STRAIGHT-IN	CAT	A	B	C	D	E	
	DA / (OCH)	2330' / (310')					NA
LNAV/VNAV	ALS/NO ALS/ RVR ALS (m)	NIL / 1600 / NIL					
LNAV	MDA / (OCH)	2420' / (400')					
CIRCLING	ALS/NO ALS/ RVR ALS (m)	NIL / 1600 / NIL			NIL / 1800 / NIL		
	MDA / (OCH)	NA					
	VIS (m)						

CHANGES: NEW CHART.