



CODING TABLE

IAC ILS Z or LOC Z RWY 35					CUIABÁ/Marechal Rondon, INTL (SBCY)							SBCY_IAC_00K		28 MAR 19	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	UBDON	IF	N/A	N/A	N/A	+4000.00	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	CIA	CIA03*	AF	N/A	R	N/A	+2600.00	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	ICB	UDUNU	CF	350.38° Mag 332.73° True	N/A	N/A	+2600.00	N/A	N/A	1.54	N/A	IF	N/A
10	APCH	N/A	N/A	LIXAP	IF	N/A	N/A	N/A	+4000.00	N/A	N/A	N/A	N/A	IAF	N/A
20	APCH	N/A	CIA	CIA04*	AF	N/A	L	N/A	+2600.00	N/A	N/A	N/A	N/A	OTHER	N/A
30	APCH	N/A	ICB	UDUNU	CF	350.38° Mag 332.73° True	N/A	N/A	+2600.00	N/A	N/A	1.69	N/A	IF	N/A
10	FINAL	N/A	N/A	UDUNU	IF	N/A	N/A	N/A	+2600.00	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N/A	ICB	XODUP	CF	350.38° Mag 332.74° True	N/A	N/A	R2230.00	N/A	N/A	5.00	N/A	FAF	N/A
30	FINAL	Y	ICB	THR35	CF	350.37° Mag 332.75° True	N/A	N/A	+641.24	N/A	N/A	5.00	-3.00	LTP/FTP	N/A
10	MA	N/A	N/A	N/A	VA	350.38° Mag 332.75° True	N/A	N/A	+1700.00	N/A	N/A	N/A	N/A	N/A	N/A
20	MA	N/A	CIA	ANLED	CF	358.41° Mag 340.81° True	R	N/A	+4000.00	230.00	-	N/A	N/A	MAHF	N/A
30	MA	N/A	CIA	ANLED	HM	178.41° Mag 160.81° True	R	N/A	+4000.00	N/A	N/A	N/A	N/A	MAHF	N/A

*For coding purpose only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
UDUNU	S 15:48:39.57W 56:01:57.35
XODUP	S 15:44:11.79W 56:04:19.89
ANLED	S 15:25:08.42W 56:11:49.91
UBDON	S 15:45:53.82W 55:56:25.56
CIA03	S 15:50:01.98W 56:01:13.59
LIXAP	S 15:51:25.18W 56:07:29.30
CIA04	S 15:50:10.28W 56:01:09.17

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT