



CODING TABLE

IAC VOR X RWY 24R					ANÁPOLIS/Base Aérea, MIL (SBAN)								SBAN_IAC_00U		23 MAY 19	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification	
10	APCH	N/A	N/A	APO	IF	N/A	N/A	N/A	+7000.00	N/A	N/A	N/A	N/A	IAF	N/A	
20	APCH	N/A	APO	APO	FC	35.23° Mag 13.96° True	N/A	N/A	+6200.00	240.00	-	10.50	N/A	OTHER	N/A	
30	APCH	N/A	APO	GUXIT	CF	240.40° Mag 219.09° True	R	N/A	R5460.00	N/A	N/A	2.69	N/A	FAF	N/A	
10	FINAL	N/A	N/A	GUXIT	IF	N/A	N/A	N/A	R5460.00	N/A	N/A	N/A	N/A	FAF	N/A	
20	FINAL	N/A	APO	AN010	CF	240.37° Mag 219.10° True	N/A	N/A	+3706.20	N/A	N/A	5.50	-3.00	LTP/FTP	N/A	
10	MA	N/A	APO	N/A	CA	240.37° Mag 219.11° True	N/A	N/A	+6000.00	N/A	N/A	N/A	N/A	N/A	N/A	
20	MA	N/A	N/A	APO	DF	N/A	R	N/A	+7000.00	N/A	N/A	N/A	N/A	MAHF	N/A	
30	MA	N/A	APO	APO	HM	35.24° Mag 13.97° True	L	N/A	+7000.00	N/A	N/A	N/A	N/A	MAHF	N/A	

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
APO	S 16:14:43.32W 48:58:44.72
GUXIT	S 16:08:37.89W 48:53:37.49
THR24R	S 16:12:55.10W 48:57:13.69

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT