



CODING TABLE

IAC ILS Z ou/or LOC Z RWY 11					PORTO ALEGRE / Salgado Filho, INTL (SBPA)							SBPA_IAC_01C		19 JUL 18	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	EDSOL	IF	N/A	N/A	N/A	+6000	N/A	N/A	N/A	N/A	IAF	NA
20	APCH	N	N/A	FIG04*	AF	N/A	L	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	NA
30	APCH	N	FIG	POSBI	CF	108.22° Mag 91.35° True	N/A	N/A	+2000	N/A	N/A	2.80	N/A	IF	NA
10	APCH	N/A	N/A	PANIB	IF	N/A	N/A	N/A	+6000	N/A	N/A	N/A	N/A	IAF	NA
20	APCH	N	N/A	FIG04*	AF	N/A	L	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	NA
30	APCH	N	FIG	POSBI	CF	108.22° Mag 91.35° True	N/A	N/A	+2000	N/A	N/A	2.80	N/A	IF	NA
10	APCH	N/A	N/A	ISTEN	IF	N/A	N/A	N/A	+5000	N/A	N/A	N/A	N/A	IAF	NA
20	APCH	N	N/A	FIG04*	AF	N/A	R	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	NA
30	APCH	N	FIG	POSBI	CF	108.22° Mag 91.35° True	N/A	N/A	+2000	N/A	N/A	2.80	N/A	IF	NA
10	APCH	N/A	N/A	VUBRA	IF	N/A	N/A	N/A	+4000	N/A	N/A	N/A	N/A	IAF	NA
20	APCH	N	N/A	FIG04*	AF	N/A	R	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	NA
30	APCH	N	FIG	POSBI	CF	108.22° Mag 91.35° True	N/A	N/A	+2000	N/A	N/A	2.80	N/A	IF	NA
10	Final	N	N/A	POSBI	IF	N/A	N/A	N/A	+2000	N/A	N/A	N/A	N/A	IF	NA
20	Final	N	IPA	MULKO	CF	108.25° Mag 91.36° True	N/A	N/A	R1750	N/A	N/A	2.19	N/A	FAF	NA
30	Final	N	IPA	SDF	CF	108.45° Mag 91.52° True	N/A	N/A	+703	N/A	N/A	3.20	N/A	SDF	NA
40	Final	N	IPA	RWY11	CF	108.46° Mag 91.50° True	N/A	N/A	+66	N/A	N/A	2.00	-3.00	LTP/FTP	NA
10	MA	N	FIG	FIG	CF	108.60° Mag 91.50° True	N/A	N/A	N/A	N/A	N/A	10.81	1.43	TP	NA

20	MA	N	FIG	AJAX	CF	139.51° Mag 122.37° True	R	N/A	+4000	N/A	N/A	N/A	N/A	MAHF	NA
30	MA	N	FIG	AJAX	HM	139.51° Mag 122.37° True	L	N/A	+4000	N/A	N/A	1.00 min	N/A	MAHF	NA

*Only for coding purpose.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
POSBI	S 29:59:29.40W 51:19:29.40
MULKO	S 29:59:32.78W 51:16:58.05
RWY11	S 29:59:39.77W 51:10:58.84
EDSOL	S 29:45:23.42W 50:41:01.30
FIG04	S 29:59:25.41W 51:22:42.61
PANIB	S 29:44:45.44W 51:15:19.36
ISTEN	S 30:15:49.67W 51:14:21.21
VUBRA	S 30:08:19.26W 51:20:42.52
AJAX	S 30:03:47.40W 50:51:28.20

COD	Meaning
+	AT OR ABOVE
N/A	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT