



CODING TABLE

IAC RNAV (GNSS) W RWY 27L					SÃO PAULO / Guarulhos - Gov. André Franco Montoro, INTL (SBGR)							SBGR_IAC_04B		SUP/SUPP AIP N120/A071 20 JUN 19 TIL 12 SET 19	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role of the Fix	Navigation Specification
10	ANSUG	N/A	N/A	ANSUG	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	ANSUG	N	N/A	ESDAR	TF	200.13° Mag 179.14° True	N/A	N/A	+5500	N/A	N/A	6.41	N/A	IF	RNP APCH
10	VURAK	N/A	N/A	VURAK	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNP APCH
20	VURAK	N	N/A	ESDAR	TF	272.66° Mag 251.68° True	N/A	N/A	+5500	N/A	N/A	6.06	N/A	IF	RNP APCH
10	FINAL	N/A	N/A	ESDAR	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IF	RNP APCH
20	FINAL	N	N/A	GR041	TF	274.59° Mag 253.66° True	N/A	N/A	+4090	N/A	N/A	5.66	N/A	FAF	RNP APCH
30	FINAL	N	N/A	RW27L*	TF	274.57° Mag 253.68° True	N/A	N/A	@2495	N/A	N/A	5.00	N/A	LTP/FTP	N/A
10	MA	N/A	N/A	N/A	VA	274.57° Mag 253.69° True	N/A	N/A	+3400	N/A	-230	N/A	N/A	OTHER	RNP APCH
20	MA	N/A	N/A	ISIMU	DF	N/A	N/A	N/A	+6000	N/A	-230	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	ISIMU	HM	130.00° Mag 109.07° True	L	N/A	+6000	N/A	-230	1.00 min	N/A	MAHF	RNP APCH

(*) Fictitious point = for coding purpose only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
ESDAR	S 23:22:51.60W 46:16:24.60
GR041	S 23:24:27.61W 46:22:18.87
ISIMU	S 23:31:14.03W 46:20:19.45
ANSUG	S 23:16:25.75W 46:16:30.86
VURAK	S 23:20:56.81W 46:10:09.57
RW27L*	S 23:25:52.28W 46:27:31.88

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT