



CODING TABLE

IAC VOR Y RWY 15					RIO DE JANEIRO / Galeão – Antônio Carlos Jobim, INTL (SBGL)							SBGL_IAC_00V		03 JAN 19	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role of the Fix	Navigation Specification
10	APCH	N/A	N/A	UTBOM	IF	N/A	N/A	N/A	+6300	N/A	N/A	N/A	N/A	IAF	---
20	APCH	N	CXI	CXI16*	CF	148.76° Mag 125.98° True	N/A	N/A	+5800	N/A	N/A	1.03	N/A	OTHER	---
30	APCH	N	CXI	EVSEX	CF	148.72° Mag 125.96° True	N/A	N/A	+3300	N/A	N/A	6.48	N/A	IF	---
10	APCH	N/A	N/A	EGDUT	IF	N/A	N/A	N/A	+6300	N/A	N/A	N/A	N/A	IAF	---
20	APCH	N	CXI	CXI16*	AF	N/A	R	N/A	+5800	N/A	N/A	N/A	N/A	OTHER	---
30	APCH	N	CXI	EVSEX	CF	148.72° Mag 125.96° True	N/A	N/A	+3300	N/A	N/A	6.48	N/A	IF	---
10	FINAL	N	N/A	EVSEX	IF	N/A	N/A	N/A	+3300	N/A	N/A	N/A	N/A	IF	---
20	FINAL	N	CXI	CXI17*	CF	148.72° Mag 125.96° True	N/A	N/A	+2500	N/A	N/A	2.00	N/A	SDF	---
30	FINAL	N	CXI	GAXUR	CF	148.72° Mag 125.90° True	N/A	N/A	R1700	N/A	N/A	2.96	N/A	FAF/FAP	---
40	FINAL	N	CXI	CXI18*	CF	148.72° Mag 125.90° True	N/A	N/A	+1022	N/A	N/A	2.10	-3.00	SDF	---
50	FINAL	N/A	N/A	CXI13**	CF	148.73° Mag 125.89° True	N/A	N/A	=67	N/A	N/A	3.00	-3.00	LTP/FTP	---
10	MA	N	CXI	UTKUP	CF	114.68° Mag 91.79° True	N/A	N/A	+3000	N/A	N/A	N/A	N/A	OTHER	---
20	MA	N	CXI	GL079*	CF	114.66° Mag 91.72° True	N/A	N/A	=4000	N/A	N/A	8.00	N/A	OTHER	---
30	MA	N	CXI	SISER	CF	114.65° Mag 91.67° True	N/A	N/A	=5000	N/A	N/A	7.00	N/A	MAHF	---
40	MA	N	CXI	SISER	HM	294.65° Mag 271.67° True	L	N/A	=5000	N/A	N/A	---	---	MAHF	---

(*) Fictitious point

(**) Fictitious point = fictitious THR15.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
EVSEX	S 22:42:56.99 W 43:24:39.07
CXI17*	S 22:44:07.63 W 43:22:53.96
GAXUR	S 22:45:52.14 W 43:20:18.33
UTKUP	S 22:49:16.80 W 43:06:56.40
SISER	S 22:49:43.80 W 42:50:42.60
UTBOM	S 22:38:31.80 W 43:31:13.20
CXI16*	S 22:39:07.89 W 43:30:18.86
EGDUT	S 22:46:27.00 W 43:33:34.20
CXI13**	S 22:48:52.43 W 43:15:49.64
CXI18*	S 22:47:06.52 W 43:18:27.49
CXI19	S 22:48:17.06 W 43:16:42.30
GL079	S 22 49 31.40 W 42 58 17.05

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT