



CODING TABLE

IAC ILS O ou/or LOC O RWY 27L					SÃO PAULO / Gov. André Franco Montoro, INTL (SBGR)							SBGR_IAC_03Z		12 SEP 19	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST	VA (°)	Role of the Fix	Navigation Specification
10	APPROACH	N/A	N/A	ANSUG	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APPROACH	N	N/A	ESDAR	TF	200.77° Mag 179.14° True	N/A	N/A	+5500	N/A	N/A	6.41	N/A	IF	RNAV 1 or RNP 1
10	APPROACH	N/A	N/A	VURAK	IF	N/A	N/A	N/A	+7000	N/A	N/A	N/A	N/A	IAF	RNAV 1 or RNP 1
20	APPROACH	N	N/A	ESDAR	TF	273.31° Mag 251.68° True	N/A	N/A	+5500	N/A	N/A	6.06	N/A	IF	RNAV 1 or RNP 1
10	FINAL	N/A	N/A	ESDAR	IF	N/A	N/A	N/A	+5500	N/A	N/A	N/A	N/A	IF	N/A
20	FINAL	N	IBC	GR041	TF	275.23° Mag 253.65° True	N/A	N/A	+4090	N/A	N/A	5.66	N/A	FAF	N/A
30	FINAL	N	IBC	THR27L*	CF	275.23° Mag 253.65° True	N/A	N/A	@2495	N/A	N/A	5.00	N/A	LTP/FTP	N/A
10	MA	N/A	N/A	N/A	CA	274.57° Mag 253.68° True	N/A	N/A	+3400	N/A	-230	N/A	N/A	OTHER	RNP APCH
20	MA	N/A	N/A	ISIMU	DF	N/A	L	N/A	+6000	N/A	-230	N/A	N/A	MAHF	RNP APCH
30	MA	Y	N/A	ISIMU	HM	130.00° Mag / 108.42° True	R	N/A	+6000	N/A	-230	1min	N/A	MAHF	RNP APCH

(*) Fictitious point = for coding purpose only.

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
IBC	S 23:26:22.65W 46:29:24.34
ESDAR	S 23:22:51.60W 46:16:24.60
GR041	S 23:24:27.61W 46:22:18.87
ISIMU	S 23:31:14.03W 46:20:19.45
ANSUG	S 23:16:25.75W 46:16:30.86
VURAK	S 23:20:56.81W 46:10:09.57
THR27L*	S 23:25:52.28 W 46:27:31.88

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE
LTP	LANDING THRESHOLD POINT
FTP	FICTITIOUS THRESHOLD POINT