



CODING TABLE

STAR RNAV EDVIV 1B RWY 29L/29R					BRASÍLIA / Pres. Juscelino Kubitschek, INTL (SBBR)							SBBR_STAR_01J		27 FEB 20	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	SIRUL	N/A	N/A	SIRUL	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	SIRUL	N	N/A	WELIN	TF	29.18° Mag 7.66° True	N/A	-30000.00	N/A	N/A	N/A	47.41	N/A	OTHER	RNAV 1 or RNP 1
10	ILPAV	N/A	N/A	ILPAV	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	ILPAV	N	N/A	WELIN	TF	55.69° Mag 34.17° True	N/A	-30000.00	N/A	N/A	N/A	58.27	N/A	OTHER	RNAV 1 or RNP 1
10	VUKEP	N/A	N/A	VUKEP	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	VUKEP	N	N/A	WELIN	TF	355.41° Mag 333.89° True	N/A	-30000.00	N/A	N/A	N/A	91.82	N/A	OTHER	RNAV 1 or RNP 1
10	PABIN	N/A	N/A	PABIN	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	PABIN	N	N/A	WELIN	TF	7.39° Mag 345.87° True	N/A	-30000.00	N/A	N/A	N/A	53.48	N/A	OTHER	RNAV 1 or RNP 1
10	COMMON	N/A	N/A	WELIN	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	COMMON	N	N/A	BR022	TF	35.54° Mag 13.95° True	N/A	N/A	+20000.00	N/A	N/A	33.33	N/A	OTHER	RNAV 1 or RNP 1
30	COMMON	N	N/A	BR033	TF	35.55° Mag 13.93° True	N/A	N/A	N/A	N/A	N/A	14.23	N/A	OTHER	RNAV 1 or RNP 1
40	COMMON	N	N/A	LUVLA	TF	35.56° Mag 13.92° True	N/A	-15000.00	N/A	N/A	N/A	10.00	N/A	OTHER	RNAV 1 or RNP 1
10	RUNWAY	N/A	N/A	LUVLA	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	RUNWAY	N	N/A	BR042	TF	75.45° Mag 53.69° True	N/A	N/A	+10000.00	230	-	22.80	N/A	OTHER	RNAV 1 or RNP 1
30	RUNWAY	N	N/A	EDVIV	TF	107.94° Mag 86.10° True	N/A	N/A	+6000.00	190	-	12.97	N/A	IAF	RNAV 1 or RNP 1

STAR RNAV MOPDA 1B RWY 29L/29R					BRASÍLIA / Pres. Juscelino Kubitschek, INTL (SBBR)							SBBR_STAR_01J		27 FEB 20	
Seq Num	Transition Identifier	Fly Over	Rec Navaid	Fix Ident	Path and Terminator	Course Angle	Turn	Upper Limit Altitude (FT)	Lower Limit Altitude (FT)	Speed Limit (KT)	Speed Limit Description	TM DST (NM)	VA (°)	Role of the Fix	Navigation Specification
10	SIRUL	N/A	N/A	SIRUL	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	SIRUL	N	N/A	WELIN	TF	29.18° Mag 7.66° True	N/A	-30000.00	N/A	N/A	N/A	47.41	N/A	OTHER	RNAV 1 or RNP 1
10	ILPAV	N/A	N/A	ILPAV	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	ILPAV	N	N/A	WELIN	TF	55.69° Mag 34.17° True	N/A	-30000.00	N/A	N/A	N/A	58.27	N/A	OTHER	RNAV 1 or RNP 1
10	VUKEP	N/A	N/A	VUKEP	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	VUKEP	N	N/A	WELIN	TF	355.41° Mag 333.89° True	N/A	-30000.00	N/A	N/A	N/A	91.82	N/A	OTHER	RNAV 1 or RNP 1
10	PABIN	N/A	N/A	PABIN	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	PABIN	N	N/A	WELIN	TF	7.39° Mag 345.87° True	N/A	-30000.00	N/A	N/A	N/A	53.48	N/A	OTHER	RNAV 1 or RNP 1
10	COMMON	N/A	N/A	WELIN	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	COMMON	N	N/A	BR022	TF	35.54° Mag 13.95° True	N/A	N/A	+20000.00	N/A	N/A	33.33	N/A	OTHER	RNAV 1 or RNP 1
30	COMMON	N	N/A	BR033	TF	35.55° Mag 13.93° True	N/A	N/A	N/A	N/A	N/A	14.23	N/A	OTHER	RNAV 1 or RNP 1
40	COMMON	N	N/A	LUVLA	TF	35.56° Mag 13.92° True	N/A	-15000.00	N/A	N/A	N/A	10.00	N/A	OTHER	RNAV 1 or RNP 1
10	RUNWAY	N/A	N/A	LUVLA	IF	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	OTHER	RNAV 1 or RNP 1
20	RUNWAY	N	N/A	BR047	TF	107.93° Mag 86.17° True	N/A	N/A	+11000.00	230	-	19.23	N/A	OTHER	RNAV 1 or RNP 1
30	RUNWAY	N	N/A	MOPDA	TF	108.07° Mag 86.21° True	N/A	N/A	+7000.00	190	-	14.24	N/A	IAF	RNAV 1 or RNP 1

Ident	Latitude / Longitude (WGS84) DD:MM:SS.SS
PABIN	S 17:47:36.00W 48:11:44.40
WELIN	S 16:55:32.40W 48:25:25.20
ILPAV	S 17:43:54.00W 48:59:42.60
BR022	S 16:23:03.76W 48:17:02.40
BR033	S 16:09:11.52W 48:13:28.54
LUVLA	S 15:59:26.73W 48:10:58.58
BR042	S 15:45:54.10W 47:51:54.10
EDVIV	S 15:45:01.37W 47:38:28.96
SIRUL	S 17:42:43.05W 48:32:02.51
BR047	S 15:58:10.20W 47:51:03.60
MOPDA	S 15:57:14.02W 47:36:18.72
VUKEP	S 18:18:15.00W 47:42:57.00

COD	Meaning
+	AT OR ABOVE
-	AT OR BELOW
@	AT
R	RECOMMENDED
B	BETWEEN
=	AS ASSIGNED
SDF	STEPDOWN FIX
Y	YES
N	NO
L	LEFT
R	RIGHT
N/A	NOT APPLICABLE